

## 30W SIP Wall Speaker NS-W130

1. 30W high power ensures clear, natural, and premium sound quality
2. Flexible power supply: PoE or DC 24V
3. Supports multiple audio codecs (OPUS, G722, G711U, G711A)
4. SIP protocol compatible, integration with VoIP and IPPBX systems
5. Dual SIP accounts, supports Direct IP Call and RTP Multicast
6. Stylish wall-mounted design with durable HIPS housing



### Specification:

#### Networking

Interface	10/100 Base-TX, RJ45
Supported Protocols	SIP, HTTP, HTTPS, IPv4, TLS, RTSP, RTP, RTCP, DHCP, DNS, NTP, TCP, UDP, IGMP, ICMP, ARP
Security	Password protection, IP address filtering, Digest authentication, User access log

#### Audio

Rated Power	30W
Speaker Unit	5" × 1 Woofer, 2" × 1 Tweeter
MAX SPL	103dB
Frequency Response	90Hz–20KHz
Sensitivity	88dB
Decoding	OPUS 48KHz, MP3 44.1KHz, G.722-ADPCM 16KHz, G.711-PCMU 8KHz, G.711-PCMA 8KHz, G726 8KHz, GSM 8KHz, LPCM-16bit-Stereo/Mono 44.1kHz

#### VoIP

Protocol	SIP (compatible with VoIP, SIP devices such as IPPBX, IP Phone)
Functions	2 SIP Accounts SIP Direct IP Call, RTP Multicast
Codecs	OPUS, G722, G711U, G711A

#### General

Dimensions	255 × 192 × 155mm
Power Supply	PoE or DC 24V
Interface	RJ45, DC Power Input, GPIO Alarm Input, Reset Button
Enclosure Material	New HIPS material, durable, anti-fade, non-deformable
Weight	3 kg
Installation	Wall Mounted
Package Includes	Network Wall Speaker Quick Star Guide